

Katanax®

X-600

X-FLUXER®

SIX POSITION ELECTRIC FUSION FLUXER



SAMPLE PREPARATION FOR XRF AND ICP ANALYSIS



SOIL



ALLOYS



SLAG



MINERALS



CERAMICS



GLASS



CEMENT

SPEX® SamplePrep®
WWW.SPEXSAMPLEPREP.COM

HIGH THROUGHPUT ELECTRIC FUSION FLUXER



Scan the QR code for more information or visit www.youtube.com/sampleprep


The Katanax X-600 X-Fluxer® is the next generation in electric fusion offering new enhanced features for unparalleled results. Our fluxers combine exceptional fusion accuracy with all the advantages of electric power combined with speed, simplicity and a robust design for the experienced or novice user.

- ① High performance furnace
 - Heating elements impervious to flux
 - No exposed metal in furnace
 - Heats up quickly
- ② Integrated auto-locking safety shield protects the user during the fusion process.
- ③ Low noise level during heating, melting and standby.
- ④ Easy clean, ceramic mold holders inert to flux. Mold holder system is user-configurable to 30, 32, 35 or 40mm molds.
- ⑤ Extraction chimneys allows for direct ventilation of halogens from each crucible position.
- ⑥ Control panel is adjustable to user's height and features a USB connection for firmware updates.

SPECIFICATIONS

- VOLTAGE: 205-250 VAC single phase
- FREQUENCY: 50-60 Hz
- MAXIMUM POWER: 4000 W
- BREAKER: built in (20A)
- WEIGHT: 95 kg / 210 lbs
- HEIGHT: 56 cm / 22"
- WIDTH: 105 cm / 41"
- DEPTH: 69 cm / 27"

HEAVY DUTY • SIMPLE • VERSATILE • S



X-600 FEATURES & BENEFITS

HIGH THROUGHPUT – Used for preparing glass disks (beads) for XRF, or for preparing peroxide or pyrosulfate fusions. You can also do solid oxidations with the X-600. This unit allows you to run 6 samples at a time achieving a throughput of up to 30 samples per hour. Since the molds are in the furnace with the crucibles you also have optimum conditions for pouring.

SAFETY – Electric fluxers are safer than gas units because gas leaks are impossible. Only a standard laboratory ventilation hood is required.

ACCURACY – Precise electric temperature control achieved by dynamic temperature profile (DTP) and individual element compensation (patents pending). Analysts will benefit from temperature homogenization across all six sample positions in the furnace offering better reproducibility and more precise analysis.

RELIABILITY – Built with the most demanding lab in mind. Its design incorporates robust heating elements, platinumware holders, industrial grade motors and electronics that withstand continuous usage.

SIMPLICITY – Sleek, intuitive, LCD touch-screen interface with icons and menus that makes the operation easy and efficient. It is entirely automated and comes pre-loaded with various fusion programs that can be used as is or customized for your particular protocol. Pre-loaded programs include Oxide, Solution, Metal, Peroxide and Ramping. All programs can be saved, renamed, deleted or copied, just like computer files. The software is also available in multiple languages.

SOLUTIONS MODULE – Optional solutions stirrer with variable speed allows the X-600 to produce solutions for ICP/AA analysis in up to 6 beakers simultaneously. Alternating between solutions mode and bead making mode requires only a simple adjustment and alternate method selection.



SAFE • ACCURATE • EASY INSTALLATION



ADVANTAGES OF THE X-600

HEATING ELEMENTS:

- Impervious to flux and other additives.
- Robust, non-brittle (instrument can be moved without element damage)
- Automatic power calibration maintains uniform position to position temperature.
- Cartridge type, (quick replacement, no need for conditioning procedures)
- Elements can be changed individually.

FURNACE:

- Individual element compensation. Allows continued operation even if one element is failing.
- Dynamic Temperature Profile (DTP) control to maintain uniform temperature (patent pending)
- Fast heat-up.
- Use of ceramics eliminates metal contamination.

OTHER FEATURES:

- Low noise during heating, melting and standby.
- Industrial PLC interface (does not depend on Windows updates)
- Single phase power (no need for 3-phase)
- No external supplies required (no power supply box, no cooling fluids, no compressed air)

METHOD DEVELOPMENT PROGRAM

Our method development program allows you to send your samples to us and our application chemists will develop a fusion protocol for you. Contact your local Katanax representative for more information.



FUSION FLUX

Superior micro-bead and pre-fused. Available with or without integrated non-wetting agents (LiBr or Lil).



PLATINUMWARE

Platinum crucibles and molds are available in standard or reinforced varieties.

SERVICE & MAINTENANCE

The X-Fluxers are designed to be operated with limited maintenance. Servicing these units is made simple with easy component access, backed up with support from our dedicated service team.



Katanax X-300 X-FLUXER®

This automated, heavy-duty, electric fusion machine has a throughput of up to 15 samples per hour. The X-300 can be pre-configured to your needs and allows the user to expand the unit to two or three positions. Used to prepare glass disks (beads) for XRF, solutions for ICP/AA and peroxide or pyrosulfate fusions. It combines speed, simplicity and a robust design ideal for the experienced or novice user.



1 POSITION



2 POSITION



3 POSITION



Scan the QR code to watch the video.

Katanax
100-2500 rue Jean-Perrin
Quebec, QC G2C 1X1 Canada
Tel: +1 (418) 915-4848
Fax: +1 (418) 657-6203
info@katanax.com
www.katanax.com

SPEX SamplePrep
65 Liberty Street
Metuchen, NJ 08840 USA
Tel: +1 (732) 623-0465
Toll Free: +1 855-GET-SPEX (855-438-7739)
sampleprep@spex.com
www.spexsampleprep.com

SPEX Europe
Trinity Court, Church Street
Rickmansworth WD3 1RT
Tel: +44 (0) 208 204 6656
Fax: +44 (0) 208 204 6654
spexeurope@spex.com
www.spexeurope.com